



BD302 BUSINESS DIGITAL RADIO

SIMPLE, ROBUST, CLEAR-VOICE



Hytera's BD302 two-way radio is the compact device that provides a professional communication in easy to operate way. Today, communication tool is the key to improve the efficiency. When we ask for clear voice, it means a reliable talk that's easy to hear and understand. Long battery life helps you to avoid losing contact. A rugged and robust device with high performance but simple to operate will make everything easier to handle.

Hytera understands customers' requirements and meets them all in one, with lightweight, easy-operation, excellent performance, long-time working and reliability. So we redefine a business radio with Hytera digital technology, quickly responding to what you need.

SUCH THIN AND LIGHT

BD302 weighs just 5oz., quite comfortable you hold it. Relief for you from busy communication in your daily work, by this pocket-sized radio.

EXCELLENT PERFORMANCE

Only 2W output power but BD302 still has amazing performance. Excellent receiving ability makes the talk range further extended. It has good performance of anti-interference in digital mode providing purely stable communication.

RUGGED AND RELIABLE

BD302 is designed and tested to meet Military Standards 810 C, D, E, F and G, including temperature shock, vibration, high & low temperature and humidity. IP54 dust- and water-proof design guarantees the reliability in multiple environments. And based on TDMA technology, the radio can work longer, up to 16 hours in digital mode.

CLEAR VOICE

With digital encoding and correction technology, human voice is transmitted much clearer without background noise, even from a rather far distance. This is a new experience of better audio quality.



PROFESSIONAL AND SIMPLE TO USE

A/D ANALOG & DIGITAL DUAL MODES
BD302 can support both analog and digital modes on the same hardware. You can switch between two operation modes very easily and it helps you to communicate with analog radios.

ANALOG & DIGITAL AUTO DETECT
BD302 can detect the signal type when receiving a call, then automatically switches between analog mode and digital mode to get the voice out of speaker. During the call hang time, user can easily reply the call by push-to-talk. This is a real migration technology from analog to digital.

EXTENDED TALK RANGE
Extend your talk range based on Hytera's innovative technology.

LONG WORKING TIME
Based on TDMA technology, BD302 in digital mode can work as long as 16 hours in 5-5-90 mode.

CLEAR VOICE
Excellent audio quality comes from the DMR digital technology, which makes the communication more reliable.

RELIABLE AND DURABLE
BD302 is compliant with MIL-STD-810 C/D/E/F/G and IP54.

ANTI-INTERFERENCE
Adopted digital encoding and error correcting module, BD302 has a better ability to avoid signal interference on the same frequency.

DMR DMR SIGNALING
With DMR signaling, transmitting group calls, private calls and all calls with PTT ID becomes quite easy.

REPEATER MODE OPERATION
Utilize a DMR Tier II repeater to extend your communication range.

VOICE ANNOUNCEMENT
Channel number announcement helps you to switch channels quickly and correctly, even in blindness operation.



DUAL CAPACITY DIRECT MODE
In direct mode, you can have two voice calls simultaneously from DMR two time slots. This feature can be used to increase the radio capacity at no extra costs or frequency license.

VOX
When using VOX earpiece, this feature allows you to activate the microphone via speaking volume, and free your hand from PTT.

SCANNING
Allow BD302 listening to communication activities on other channels.

ACCESSORIES

STANDARD ACCESSORIES

 <p>AN0435H19 Antenna, 400-470MHz, 9cm</p>	 <p>BL2202 2200mAh Li-ion Battery</p>	 <p>BC16 Belt clip</p>	 <p>RO03 Nylon hand strap</p>	 <p>Power Adapter input: 100-240VAC, output: 12VDC/1A <i>US/UK/AU/EU/CHINA/JAPAN/KOREA</i></p>
--	---	--	--	--

OPTIONAL ACCESSORIES

 <p>ACS-01 PTT&MIC-only with 3.5mm jack <i>IP54</i></p>	 <p>ES-01 Receive-only ear-bud</p>	 <p>ES-02 Receive-only surveillance earpiece</p>	 <p>EH-01 Receive-only C style earpiece</p>	 <p>EH-02 Receive-only earhook speaker</p>
 <p>ESH16 C-style Earpiece with in-line PTT & MIC</p>	 <p>VOX earpiece coming soon</p>	 <p>CH10L22 Bd300 Standard Drop-In Single Unit Charger</p>	 <p>PV1002 Vehicle adapter (Input: 11-25V DC, Output: 12V DC & 1A)</p>	 <p>PC69 Data programming cable</p>



SPECIFICATION

General	
Frequency Range	UHF:400-470 MHz
Channel Capacity	48
Zone Capacity	3
Channel Spacing	25/12.5KHz
Operating Voltage	3.8V
Battery	2200mAh (Li-Ion)
Battery Life (5/5/90)	Analog/Digital: 12/16 hours (2200mAh) 16/22 hours (2000mAh)
Weight	5 oz. (with AN0435H19 and BL2202)
Dimensions	101×49×25.8mm
Frequency Stability	± 0.5ppm
Antenna Impedance	50 Ω

Receiver		
Sensitivity (Digital)		0.22 μV / BER 5%
Sensitivity (Analog)		0.22 μV (Typical) (12dB SIN AD) 0.4 μV (20dB SIN AD)
Adjacent Selectivity	TIA-603	60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603	70dB @ 12.5/25KHz
Inter-modulation	TIA-603	65dB @ 12.5/25KHz
Hum & Noise		40dB @ 12.5KHz 45dB @ 25KHz
Rated Audio Power Output		0.5W
Rated Audio Distortion		≤5%
Audio Response		+1 ~ -3dB
Conducted Spurious Emission		<-57dBm

Transmitter	
RF Power Output	High power: 2W Low power: 1W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	± 2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤5%
Digital Vocoder Type	AMBE++
Digital Protocol	ETSI-TS102 361-1,-2,-3

Environmental	
Operating Temperature	-30°C~ +60°C
Storage Temperature	-40°C~ +85°C
ESD	IEC 61000-4-2 (Level 4) ± 8kV (Contact) ± 15kV (Air)
Dustproof & Waterproof	Ip54 Standard
Humidity	Per MIL-STD-810 C/D/E/F/G Standard
Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard

All specifications are subject to change without notice due to continuous development.



Hytera America

Address: 3315 Commerce Parkway
Miramar, Florida 33025

Tel: 800-845-1230 **Fax:** 954-846-1672

<http://www.hytera.us>

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Co.,Ltd.

© 2013 Hytera Communications Co.,Ltd. All Rights Reserved.